

ZR45K3E-PFJ

HFC, R-407C, Mid Point, 50 Hz, 1 - Phase, 220/240 V
Air Conditioning

Performance

<u>Evap(°F)/Cond(°F)</u>	<u>45/130</u>	<u>45/100</u>
<u>RG(°F)/Liq(°F)</u>	<u>65/115</u>	<u>65/85</u>
Capacity (Btu/hr):	38600	47400
Power (Watts):	3560	2440
Current (Amps):	17.3	12.4
EER (Btu/Wh):	10.8	19.4
Mass Flow (lbs/hr):	570.0	600.0
Sound Power(dBA):	68 Ave	73 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2005-01-03	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	3.726
Bore Size (in):	0.0	Displ (ft ³ /hr):	375.1858
Stroke (in):	0.0		
Overall Length (in):	9.52	Mounting Length (in):	7.5
Overall Width (in):	9.52	Mounting Width(in):	7.5
Overall Height (in):	16.95	Mounting Height (in):	17.18*
Suction Size (in):	7/8 Stub		
Discharge Size (in):	1/2 Stub		
Initial Oil Charge (oz):	42		
Oil Recharge (oz):	38		
Net Weight (lbs):	71.0		
Internal Free Volume (in ³):			
HorsePower	3.5		
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	114.0	MCC (Amps):	27.0	UL File No.:	
LRA-Half Winding:		RPM:	2900	UL File Date:	14-Jun-1994
LRA-Low*:	105.0	Max Operating Current:	22.5	CSA File No.:	
RLA(=MCC/1.4; use for contactor selection): 19.3					
RLA (=MCC/1.56; use for breaker & wire size selection): 17.3					
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407C HFC	60	1	265	Air Conditioning