

ZR47K3E-PFJ

HFC, R-407C, Dew Point, 50 Hz, 1 - Phase, 220/240 V
Air Conditioning

Performance

Evap(°F)/Cond(°F)	<u>45/130</u>	<u>45/100</u>
RG(°F)/Liq(°F)	<u>65/115</u>	<u>65/85</u>
Capacity (Btu/hr):	37400	45300
Power (Watts):	3480	2350
Current (Amps):	16.9	12.3
EER (Btu/Wh):	10.7	19.3
Mass Flow (lbs/hr):	545.0	560.0
Sound Power(dBA):	68 Ave 73 Max	
Vibration (mils(peak-peak)):	2.0 Ave 3.0 Max	
Record Date:	2005-04-15	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	3.864
Bore Size (in):	0.0	Displ (ft ³ /hr):	389.0816
Stroke (in):	0.0		
Overall Length (in):	9.567	Mounting Length (in):	7.5
Overall Width (in):	9.567	Mounting Width(in):	7.5
Overall Height (in):	16.95	Mounting Height (in):	17.18*
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Initial Oil Charge (oz):		42	
Oil Recharge (oz):		38	
Net Weight (lbs):		69.0	
Internal Free Volume (in ³):		205.0	
HorsePower		4.0	
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	114.0	MCC (Amps):	27.0	UL File No.:	
LRA-Half Winding:		RPM:	2900	UL File Date:	14-Jun-1994
LRA-Low*:	105.0	Max Operating Current:	22.7	CSA File No.:	
RLA(=MCC/1.4; use for contactor selection): 19.3					
RLA (=MCC/1.56; use for breaker & wire size selection): 17.3					
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-134a HFC	60	1	265	Air Conditioning
R-407C HFC	60	1	265	Air Conditioning
R-134a HFC	50	1	220/240	Air Conditioning