

ZR48KCE-TFD

HFC, R-407C, Dew Point, 50 Hz, 3 - Phase, 380/420 V
Air Conditioning

Performance

Evap(°F)/Cond(°F)	<u>45/130</u>	<u>45/100</u>
RG(°F)/Liq(°F)	<u>65/115</u>	<u>65/85</u>
Capacity (Btu/hr):	38600	46800
Power (Watts):	3590	2410
Current (Amps):	6.3	4.8
EER (Btu/Wh):	10.7	19.4
Mass Flow (lbs/hr):	560.0	580.0
Sound Power(dBA):	71 Ave	76 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2005-04-15	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	3.997
Bore Size (in):	0.0	Displ (ft ³ /hr):	402.4739
Stroke (in):	0.0		
Overall Length (in):	9.567	Mounting Length (in):	7.5
Overall Width (in):	9.567	Mounting Width(in):	7.5
Overall Height (in):	16.95	Mounting Height (in):	17.18*
Suction Size (in):	0		
Discharge Size (in):	0		
Initial Oil Charge (oz):	46		
Oil Recharge (oz):	42		
Net Weight (lbs):	62.0		
Internal Free Volume (in ³):	177.0		
HorsePower			
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	50.0	MCC (Amps):	11.0	UL File No.:	SA-2337
LRA-Half Winding:		RPM:	2900	UL File Date:	14-Jun-1994
LRA-Low*:		Max Operating Current:	10.0	CSA File No.:	LR3104C
RLA(=MCC/1.4; use for contactor selection):	7.9				
RLA (=MCC/1.56; use for breaker & wire size selection):	7.1				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-134a HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-134a HFC	50	3	380/420	Air Conditioning