

ZR81KCE-TFD

HFC, R-407C, Dew Point, 50 Hz, 3 - Phase, 380/420 V
Air Conditioning

Performance

Evap(°F)/Cond(°F)	45/130	45/100
RG(°F)/Liq(°F)	65/115	65/85
Capacity (Btu/hr):	63500	77000
Power (Watts):	5900	3990
Current (Amps):	10.9	8.6
EER (Btu/Wh):	10.8	19.3
Mass Flow (lbs/hr):	925.0	955.0
Sound Power(dBA):	72 Ave	77 Max
Vibration (mils(peak-peak)):	2.0 Ave	3.0 Max
Record Date:	2005-04-15	

Mechanical

Number of Cylinders:	0	Displ (in ³ /Rev):	6.577
Bore Size (in):	0.0	Displ (ft ³ /hr):	662.2644
Stroke (in):	0.0		
Overall Length (in):	9.48	Mounting Length (in):	7.5
Overall Width (in):	9.71	Mounting Width(in):	7.5
Overall Height (in):	17.955	Mounting Height (in):	18.205*
Suction Size (in):	7/8 Stub		
Discharge Size (in):	3/4 Stub		
Initial Oil Charge (oz):	60		
Oil Recharge (oz):	56		
Net Weight (lbs):	86.0		
Internal Free Volume (in ³):	258.0		
HorsePower			
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	101.0	MCC (Amps):	17.0	UL File No.:	SA-2337
LRA-Half Winding:		RPM:	2900	UL File Date:	26-Jul-1993
LRA-Low*:	90.5	Max Operating Current:	15.0	CSA File No.:	LR3104C
RLA(=MCC/1.4; use for contactor selection):	12.1				
RLA (=MCC/1.56; use for breaker & wire size selection):	10.9				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Frequency(Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-134a HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-134a HFC	50	3	380/420	Air Conditioning